Yuasa Technical Data Sheet


Yuasa NP7-12FR Industrial VRLA Battery

Specifications Nominal voltage (V) 10-hr rate Capacity to 1.8V/Cell at 20°C (Ah) 20-hr rate Capacity to 1.75V/Cell at 20°C (Ah)	12 6.4 7
Dimensions Length (mm) Width (mm) Height over terminals (mm) Mass (kg)	151 (±1) 65 (±1) 97.5 (±2) 2.2
Terminal Type FASTON - Quickfit / release (JST where stated)	4.75
Operating Temperature Range Storage (in fully charged condition) Charge Discharge	-20°C to +60°C -15°C to +50°C -20°C to +60°C
Storage Capacity loss per month at 20°C (% approx.)	3
Case Material Standard	ABS (UL94:V0)
Charge Voltage Float charge voltage at 20°C (V)/Block Float charge voltage at 20°C (V)/Cell Float Chg voltage tmp correction factor from std 20°C (mV)	13.65 (±1%) 2.275 (±1%) -3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block Cyclic (or Boost) charge Voltage at 20°C (V)/Cell Cyclic Chg voltage tmp correction factor from std 20°C (mV)	14.5 (±3%) 2.42 (±3%) -4
Charge Current Float charge current limit (A) Cyclic (or Boost) charge current limit (A)	No limit 1.75
Maximum Discharge Current 1 second (A) 1 minute (A)	210 48
Impedance Measured at 1 kHz (mΩ)	23





Layout



3rd Party Certifications ISO9001 - Quality Management Systems



Safety

Installation

3 to 5 years

up to 5

Can be installed and operated in orientations up to 90° from the upright position.

Handles

Batteries must not be suspended by their handles (where fitted).

Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.



Data Sheet generated on 20/01/2025 - E&OE

EUROBAT Classification: Standard Commercial

Design Life & Approvals

Yuasa design life at 20°C (yrs)

The world's leading battery manufacturer

www.yuasaeurope.com

